


DOOR

DOUBLE HINGED

Double leaf hinged doors, with zinc coated iron hinges, can be built using all Accesssafe ranges of framed panels. The door can be pre assembled at our factory, or it can be supplied as Door in a Box, to be assembled on site. Posts and assembly accessories are supplied but door panels need to be purchased separately. All doors have floor fixing plugs and include UNI EN ISO 14120 captive bolts.




LOCKS



GAMMA

High quality lock with aluminum housing and stainless steel mechanism. It is supplied with a set of 2 anodized aluminum handles. Key lock is available upon request.


COMPATIBILITY: DEDICATED PANELS IN 30mm TUBULAR



BARREL BOLT LOCK

Mechanic lock with horizontal sliding barrel bolt with handle included.

COMPATIBILITY: ALL FRAMED PANELS



NEUTRAL


Lock-free system for optional fitting of accessories such as a safety push bar or safety electronic locks.

COMPATIBILITY: ALL FRAMED PANELS

CROSSPIECE



WITH






WITHOUT

COMPATIBILITY

Doors are compatible with guard systems built with framed panels and META or VITERIA posts

COLOURS (RAL)

All doors undergo epoxy coating process.


-  9005
-  1018
-  7035

Other colours upon request.

BASE, TUBULAR AND FLOOR FITTING

WELDED BASE


ADJUSTABLE BASE



40x40 2 M8 galvanized steel mechanic plugs

60x60 4 M8 galvanized steel mechanic plugs


PLATE SIZE: 192x100mm



40x40 2 M8 galvanized steel mechanic plugs

Height setting 18mm


PLATE SIZE: 35x155mm



60x60 4 M8 galvanized steel mechanic plugs


Height setting 25mm

PLATE SIZE: 192x100mm



80x80 4 M8 galvanized steel mechanic plugs


PLATE SIZE: 200x200mm



80x80 4 M8 galvanized steel mechanic plugs

Height setting 25mm

PLATE SIZE: 200x200mm



80x80 4 M8 galvanized steel mechanic plugs

Height setting 40mm

PLATE SIZE: 200x200mm

CODE STRUCTURE

VFDA. B **D** **C** **C** **B** **R** **2** **.1400** **2020**

