

PANELS

POLYCARBONATE RANGE

Polycarbonate machinery safety guards are 4mm thick and have a riveted sheet fixed to frame. Frames come in two sizes:

FRAME
mm

20


FRAME
mm

30

These guards are employed when the danger area is close and prevention from dust, sparks or liquid leaks is needed yet visibility within danger area is guaranteed. Distance from danger area can be as little as 0mm.

The panel is provided with a standard hole to house toughening captive fixing screws and other accessories.

POLYCARBONATE THICKNESS: 4mm






COMPATIBILITY

Panel fixing system - META posts and VITERIA posts

COLOURS (RAL)

Panels undergo epoxy coating

-  9005
-  1018
-  7035

Other colours upon request

* For guards at a height lower than 1400 mm, extra safety measures apply as required by UNI EN ISO 13857 standard.

CODE STRUCTURE

VFPA. ^① **PO** ^② **04** ^③ **20** ^④ **.0250** ^⑤ **0960**

①	PANEL	
	PO	Polycarbonate Range
②	THICKNESS (mm)	
	04	4mm
③	FRAME SECTION (mm)	
	20	20x20
	30	30x30
④	BASE (mm)	
	250 400 700 800 1000 1200 1500	
⑤	HEIGHT (mm)	
	960 1300 1900 2100 2400	

ISO 14120

Statement of conformity TÜV Nord : DM - 124554-17
in combination with META posts

Self-certification
in combination with VITERIA posts

ISO 3834-3

Welding 3834-3 ICIM : 3834-100009-00

Impact test UNI EN ISO 14120



Accessafe Protection guards have passed the dynamic resistance test from impacts outside the danger area. Test was performed using the PENDULUM TEST procedure as required by **UNI EN ISO 14120** standard.