

PANELS

RT RANGE


RT electro-welded mesh machinery protection guard have 60x11mm mesh and 3mm thread. Frames come in two sizes:



Penta protection guards are employed to safeguard plants and machinery whose distance from danger area must be equal or above 20mm.

The panel provides a standard fixing hole for captive screws and other accessories.

MESH: 60x11mm 3mm thread




COMPATIBILITY

Panel fixing system - META posts and VITERIA posts

COLOURS (RAL)

Panels undergo epoxy coating



Other colours upon request

* For guards at a height lower than 1400 mm, extra safety measures apply as required by UNI EN ISO 13857 standard.

CODE STRUCTURE

VFPA. RE RT 20 .0250 0960

① ② ③ ④

①	PANEL
RT	RT Range
②	FRAME SECTION (mm)
20	20x20
30	30x30
③	BASE (mm)
250 400 700 800 1000 1200	
④	HEIGHT (mm)
960 1300 1900 2100 2400	

ISO 14120

Statement of conformity TÜV Nord : DM - 124554-17
in combination with META posts

Self-certification
in combination with VITERIA posts

Impact test UNI EN ISO 14120



Accessafe Protection guards have passed the dynamic resistance test from impacts outside the danger area. Test was performed using the PENDULUM TEST procedure as required by UNI EN ISO 14120 standard.