SLIDING DOOR

UPPER BINARY DOUBLE OPENING

The upper binary double opening sliding door, featuring an extra-strong aluminum rail fitted to the posts with special quills, can be built using any of Accessafe framed panels. This door can be pre-assembled in the factory or ordered as Door in a Box. Accessories and posts for assembly are supplied whereas the door panels need to be purchased separately. All doors are provided with floor fixing plugs and captive bolts as per UNI EN ISO14120.



LOCKS



GAMMA


High quality lock with aluminum housing and stainless steel mechanism. It is supplied with a set of 2 anodized aluminum handles. Key lock is available upon

COMPATIBILITY: DEDICATED PANELS IN 30mm TUBULAR



MAGNETIC

Magnetic locking system COMPATIBILITY: ALL FRAMED PANELS



NEUTRAL

Lock-free system for optional fitting of accessories such as a safety push bar or safety electronic locks

COMPATIBILITY: ALL FRAMED PANELS

BASE, TUBULAR AND FLOOR FITTING

ADJUSTABLE BASE

WELDED BASE _

40x40 ^{2 M8} galvanized steel mechanic plugs


60x60 ^{4 M8} galvanized mechanic plugs

PLATE SIZE: 192x100mm



40x40 ^{2 M8} galvanized steel mechanic plugs

Height setting 18mm




60x60 ^{4 M8} galvanized steel mechanic plugs

Height setting 25mm



80x80 4 M8 galvanized st

PLATE SIZE: 200x200mm



80x80 4 M8 galvanized stee

Height setting 25mm PLATE SIZE: 200x200mm



80x80 4 M8 galvanized mechanic plugs

Height setting 40mm PLATE SIZE: 200x200mm

COMPATIBILITY

Doors are compatible with guard systems built with framed panels and META or VITERIA posts

COLOURS (RAL)

All doors undergo epoxy coating process.







Other colours upon request.



CODE STRUCTURE

