
# **SLIDING DOOR**

# ROLLER BEARINGS AND WHEELS SINGLE OPENING

The single opening roller bearings and wheels sliding door, featuring ogives which get the door to slide, can be built using any of Accessafe framed panels. The door can be ordered as Door in a Box to be assembled on-site. Accessories and posts for assembly are supplied whereas the door panels need to be purchases separately in T30 version. All doors are provided with floor fixing plugs and captive bolts as per UNI EN ISO14120.



## **LOCKS**



## GAMMA

High quality lock with aluminum housing and stainless steel mechanism. It is supplied with a set of 2 anodized aluminum handles. Key lock is available upon request.


COMPATIBILITY: DEDICATED PANELS IN 30mm TUBULAR



#### DOUBLE BALL CATCH

Brass mechanic groove and tongue lock.

COMPATIBILITY: ALL FRAMED PANELS



#### NEUTRAL

Lock-free system for optional fitting of accessories such as a safety push bar or safety electronic locks.

COMPATIBILITY: ALL FRAMED PANELS

#### COMPATIBILITY

Doors are compatible with guard systems built with framed panels and META or VITERIA posts

# **COLOURS (RAL)**

All doors undergo epoxy coating process.



7035

Other colours upon request.

#### BASE, TUBULAR AND FLOOR FITTING

WELDED BASE \_

**60x60** 4 M8 galvanized steel mechanic plugs

PLATE SIZE: 192x100mm



ADJUSTABLE BASE \_\_\_

**60x60** 4 M8 galvanized steel mechanic plugs

Height setting 25mm

PLATE SIZE: 192x100mm



#### **CODE STRUCTURE**

1 2 3 4 5 VFDA. S C 1A 0 A R 3 .01 2020 **OPENING** 1A Single opening 2 LOCK N Latch G Gamma 0 Neutral housing (3) **TUBULAR SECTION AND POST BASE** С 60x60 post with adjustable base D 60x60 post with welded base 4 PANEL COMPATIBILITY R Mesh panel С Closed panel 0 No need to identify (5) FRAME (mm) 30x30 **6 OPENING WIDTH** 01 From 1000 to 1100mm 02 From 1105 to 1200mm 03 From 1205 to 1300mm From 1305 to 1400mm 04 From 1405 to 1500mm 05 06 From 1505 to 1600mm From 1605 to 1800mm 07 08 From 1805 to 2000mm From 2005 to 2100mm 09 10 From 2105 to 2300mm From 2305 to 2500mm 7 **HEIGHT** (mm) 1080 | 1420 | 2020 | 2220 | 2520

