SLIDING DOOR


UPPER BINARY

SINGLE OPENING

The upper binary single opening sliding door, featuring an extra-strong aluminum rail fitted to the posts with special quills can be built using any of Accessafe framed panels. This door can be pre-assembled in the factory or ordered as Door in a Box. Accessories and posts for assembly are supplied whereas the door panels need to be purchased separately. All doors are provided with floor fixing plugs and captive bolts as per UNI EN ISO14120



LOCKS



GAMMA

High quality lock with aluminum housing and stainless steel mechanism. It is supplied with a set of 2 anodized aluminum handles. Key lock is available upon

COMPATIBILITY: DEDICATED PANELS IN 30mm TUBULAR



DOUBLE BALL CATCH

Brass mechanic groove and tongue lock

COMPATIBILITY: ALL FRAMED PANELS



NEUTRAL

Lock-free system for optional fitting of accessories such as a safety push bar or safety electronic locks

COMPATIBILITY: ALL FRAMED PANELS

BASE, TUBULAR AND FLOOR FITTING

WELDED BASE _



40x40 ^{2 M8} galvanized steel mechanic plugs

60x60 ^{4 M8} galvanized steel mechanic plugs PLATE SIZE: 192x100mm

80x80 ^{4 M8} galvanized steel

80x80 ^{4 M8} galvanized stee Height setting 25mm

PLATE SIZE: 200x200mm

ADJUSTABLE BASE



40x40 ^{2 M8} galvanized steel mechanic plugs

Height setting 18mm



60x60 4 M8 galvanized steel mechanic plugs

Height setting 25mm



80x80 4 M8 galvanized steel

Height setting 40mm PLATE SIZE: 200x200mm

COMPATIBILITY

Doors are compatible with guard systems built with framed panels and META or VITERIA posts

COLOURS (RAL)

All doors undergo epoxy coating process.





Other colours upon request.



CODE STRUCTURE

1 2 3 4 5 6 .01 2020 VFDA. S S 1A O 2 A R (1)**OPENING** Single opening (2) LOCK N Latch G Gamma Neutral housing (3) **TUBULAR SECTION AND POST BASE** A 40x40 post with adjustable base В 40x40 post with welded base С 60x60 post with adjustable base D 60x60 post with welded base Ε 80x80 post with high adjustable base 80x80 post with low adjustable base F G 80x80 post with welded base 4 PANEL COMPATIBILITY R Mesh panel С Closed panel 0 No need to identify (5) FRAME (mm) 2 20x20 30x30 3 6 **OPENING WIDTH** 01 From 600 a 750mm From 755 a 950mm 02 03 From 955 a 1150mm 04 From 1155 a 1450mm 05 From 1455 a 1750mm 06 From 1755 a 1950mm 07 From 1955 a 2350mm 08 From 2355 a 2650mm 09 From 2655 a 2950mm 7 **HEIGHT** (mm) 2020 | 2220 | 2520

